



Civil aviatory

Dimension type	Bore diameter at rim seat, mm	Type of hermetization of tyre	Special factors of mounting on axle	Destination	Mass of tyre, kg	TU (Technical Conditions)
400x150-5 1A	127	Tubeless	nose-mounted	M101T "Gzhel", Yak-152	3,1	TU 38.304160-2005
500x150-9 5A	228,6	Tubeless	basic	M101T "Gzhel", Yak-152	6,5	TU 38.304159-2005
600x155 5A	305	Tube type	tail-mounted	IL-62	11,2	TU 38.404276-94
600x220-254 1A	254	Tubeless	nose-mounted	An-38, IL-112	10,5	TU 38.404276-94
				An-38-200, An-140 and modif.		TU 38.30493-2000
810x320-330 1A	330,2	Tubeless	basic	An-38	23,4	TU 38.404276-94
810x320-330 2A	330	Tubeless	basic	An-140, An-38-200 and modif.	24,9	TU 38.30493-2000
880x315 2A	361	Tubeless	basic	IL-114, IL-112	27,5	TU 38.404276-94
1050x390 6A	404	Tube type	-	Jetway f.Tissen-Henschel	79	TU 2525-015-05766824-2008
1070x390 R480 4A	481,4	Tubeless	basic	TU-204, TU-214	67	TU 38.304141-2002
1120x450 9A	482,6	Tubeless	nose-mounted	An-225	94	TU 38.304120-2001
1290x490-510 2A	557	Tubeless	basic	IL-96-400	110	TU 38.30403-2008
1300x480-560 1A	558,8	Tubeless	nose-mounted basic	IL-96, IL-96-300, IL-96-400	106	TU 38.404276-94



Aviatyres of double destination



Dimension type	Bore diameter at rim seat, mm	Type of hermetization of tyre	Special factors of mounting on axle	Destination	Mass of tyre, kg	TU (Technical Conditions)
300x125 5A	90	Tube type	nose-mounted	Mi-1, Mi-2, Ka-26, Ka-126	2,7	TU 38.404276-94
			front-mounted	Ka-226		TU 38.304148-2003
310x135 6A	100	Tube type	nose-mounted	IL-103	3,18	TU 38.404276-94
400x150 5A	115	Tube type	nose-mounted	Yak-18, Yak-52, Yak-54	4,49	TU 38.404276-94
			basic	Yak-55, IL-103 Ansatz and modif.		
400x150 7A	115	Tube type	nose-mounted	Ka-50, Ka-52, Ka-25, Ka-252 and modif.	4,79	TU 38.404276-94
400x150 8A	115	Tube type	basic	Su-29, Su-31, IL-103	4,49	TU 38.404276-94
470x210 5A	127	Tube type	tail-mounted	An-2, An-3	7,6	TU 38.404276-94
480x200 14A	152.6	Tube type	nose-mounted	MiG-15, MiG-17, Mi-14, Mi-24 and modif. Ka-25, Ka-27, Ka-31 and modif., Mi-28	6,5	TU 38.404276-94
500x150 6A	230	Tube type	main	Yak-18, Yak-50, Yak-52	5,85	TU 38.404276-94
595x185 14A	280	Tube type	nose-mounted	Mi-8 and modif., Mi-9, 19, 17 and modif., An-28	9,2	TU 38.404276-94

Dimension type	Bore diameter at rim seat, mm	Type of hermetization of tyre	Special factors of mounting on axle	Destination	Mass of tyre, kg	TU (Technical Conditions)
595x185 14A	280	Tube type	basic	Yak-12 and modif., Ka-26, 126	9,2	TU 38.404276-94
				Ka-226		TU 38.304148-2003
600x180 13A	280	Tube type	basic	Mi-2, Mi-14 and modif., Ansat and modif.	10,4	TU 38.404276-94
				Ka-25 Ka-252	11,2	TU 38.404276-94
620x180 3A	305	Tube type	nose-mounted	Su-15	14,5	TY 38.404276-94
			basic	D2, Ka-27, Ka-28, Ka-31, Ka-32		
620x180 4A	305	Tubeless	front-mounted	Su-30, Su-35 T-50, Be-200	15,5	TU 2525-089-05766824-2011
660x200 11A	335	Tube type	front-mounted nose-mounted	Su-15, Su-17, Su-20, Su-22, Su-24, Su-25 and modif., Tu-134 and modif., MiG-31	16,8	TU 38.404276-94
700x250 6A	356	Tube type	nose-mounted	An-32 and modif. An-14, An-24 and modif., An-26, IL-18, Ka-50, Ka-52, M-15	16,6	TU 38.404276-94
			basic	An-14, Mi-4		
720x310 5A	247,7	Tube type	nose-mounted	Mi-6, Yak-40, An-72, An-74 and modif.	21,1	TU38.404276-94
720x320 3A	247,7	Tube type	basic	Mi-24 and modif., Mi-28, An-28, M-15	21,1	TU 38.404276-94
800x225 12 A	406,5	Tube type	nose-mounted basic	IL-18, IL-38, Tu-154 and modif.	24,9	TU 38.404276-94
800x260 18A	330	Tube type	basic	An-2, An-3, Rysachok	25,3	TU 38.404276-95
840x290 3A	361	Tubeless	nose-mounted	Tu-214, Tu-204.300	32	TU 38.304125-2001
				Tu-204		TU 38.404276-94
865x280 1A	430	Tube type	basic	IL-14, Mi-8 and modif., Mi-9, Mi-17 and modif., Mi-19 and modif., Mi-171 and modif., Mi-172 and modif.	28,7	TU 38.404276-94



Aviatyres of double destination



Dimension type	Bore diameter at rim seat, mm	Type of hermetization of tyre	Special factors of mounting on axle	Destination	Mass of tyre, kg	TU (Technical Conditions)
900x300 8A	370	Tube type	front-mounted	Mi-26	34	TU 38.404276-94
			nose-mounted	An-8, An – 12 and modif.		
			basic	An-24 and modif.		
930x305 10A	406	Tube type	basic	IL-18, IL-38, Tu-134, Tu-154, Yak-42	37,3	TU 38.404276-94
			front-mounted	IL-62, Yak-42		
930x305 14A	406	Tube type	basic	Yak-42, Tu-134, Tu-154, IL-18, IL-20, IL-22, IL-38	37,3	TU 38.404276-94
			nose-mounted	Yak-42		
950x300 2A	468	Tubeless	basic	Tu-154, Su-24, MiG-31	47	TU 38.404276-94
				Be-200		TU 38.304126-2003
950x350 11A	451	Tube type	basic	An-8	34,5	TU 38.404276-94
			tail-mounted	Be-12		
1050x300 7A	508	Tube type	basic	An-12 and modif.	46,3	TU 38.404276-94

Dimension type	Bore diameter at rim seat, mm	Type of hermetization of tyre	Special factors of mounting on axle	Destination	Mass of tyre, kg	TU (Technical Conditions)
1050x390 1A	406,4	Tubeless	basic	An-32	45	TU 38.404276-94
1050x390 2A	406,4	Tubeless	basic	An-72, An-74 and modif.	50	TU 38.404276-94
1050x400 1A	370	Tube type	basic	An-26	45	TU 38.404276-94
1100x330 26A	508	Tubeless	nose-mounted	IL-76 and modif., IL-78	55,5	TU 38.404276-94
1120x450 3A	480	Tube type	basic	Yak-40, Mi-26 and modif.	69	TU 38.404276-94
1120x450 5A	482,6	Tubeless	nose-mounted	An-124	80	TU 38.404276-94
1120x450 10A	481,6	Tubeless	nose-mounted basic	An-70	61,5	TU 38.304195-90
			basic	An-178		
1270x510 1A	558,8	Tubeless	basic	An-124	111	TU 38.404276-94
1270x510 2A	558,8	Tubeless	basic	An-225, An-124-100 and modif.	125	TU 38.304120-2001
1300x480 1A	508	Tube type	basic	IL-76 and modif., IL-78	90	TU 38.404276-94
1300x480 4A	508	Tubeless	nose-mounted basic	IL-86	103	TU 38.404276-94
1325x480 1A	635	Tube type	basic	Mi-6	85,2	TU 38.404276-94
1450x580 2A	508	Tube type	nose-mounted	An-22	110	TU 38.404276-94
1450x450 6AM	630	Tube type	basic	IL-62	128,2	TU 38.404276-94
1750x730-610 1A	610	Tube type	basic	An-22	188	TU 38.404276-94

